



BASAK

2060 BB ORCHARD

TECHNICAL SPECIFICATIONS

ENGINE	2WD	4WD
Engine Type	ITL 3100 FLT	
Emission Type	Stage 3A	
Aspiration	Turbo / Intercooler	
Cubic Capacity/Number of Cylinders (cm ³ / Number)	2780 / 3	
Max. Engine Power (ISO 14396) (kw/hp/rpm)	43 / 58 / 2100	
Max Torque (Nm / rpm)	230 / 1300	
Engine Cooling System	Water Cooled	
Fuel Capacity (lt)	67,5	
TRANSMISSION		
Gearbox Type	Mechanical Synchromesh	
Number of Speeds	16 + 8	
4WD Actuation	-	Mechanical
Front Differential Lock System	-	Limited Slip
Rear Differential Lock System	Mechanically Controlled	
Clutch	Double Plate Dry Type (with independent control for PTO)	
HYDRAULIC SYSTEM		
Functions	Position - Power - Mixed	
Hydraulic Power Output Valves	4	
Lifting Capacity (kg)	2600	
Three Point Hitch System	Category II	
POWER TAKE OFF		
Type	Independent Double Speed	
Pto (rpm)	540 (1956)	
Pto (rpm)	540E (1506)	
BRAKES		
Type	Oil Bath Disc Brake	
Foot Brake	Mechanically Controlled	
Hand Brake	Mechanically Controlled	
TYRES		
1. Option (Front)	6,50 - 16	260/70R16
1. Option (Rear)	380/70R24	380/70R24
2. Option (Front)	6,50 - 16	280/70R18
2. Option (Rear)	380/70R28	380/70R28
DIMENSIONS (mm)		
Length	3870	3880
Height	2370	2377
Wheelbase	2075	2034
Track Width (Front) (mm)	1320 / 1420	1340
Track Width (Rear) (mm)	1285	
Ground Clearance	338	338
WEIGHTS (kg)		
Front Weights	2x30 + 50	6x30 + 50
Rear Weights	2x50	
Total Weight (Without Ballasts)	2460	2660