



BASAK

2075 BK CLASSIC

TECHNICAL SPECIFICATIONS

ENGINE	2WD (Platform)	4WD (Platform)	2WD (Cabin)	4WD (Cabin)
Engine Type	BT40845T3			
Emission Type	Stage 3A			
Aspiration	Turbo / Intercooler			
Cubic Capacity / Number of Cylinders (cm ³ /Number)	3142 / 4			
Max. Engine Power (ISO 14396) (kw/hp/rpm)	53 / 72 / 2500			
Max Torque (Nm / rpm)	273 / 1600			
Engine Cooling System	Water Cooled			
Fuel Capacity (lt)	72			
TRANSMISSION				
Gearbox Type	Mechanical Synchromesh			
Number of Speeds	16 + 8			
4WD Actuation	-	Mechanical	-	Mechanical
Front Differential Lock System	-	Limited Slip	-	Limited Slip
Rear Differential Lock System	Mechanically Controlled		Mechanically Controlled	
Clutch	Double Plate Dry Type (with independent control for PTO)			
HYRAULIC SYSTEM				
Functions	Position - Power - Mixed			
Hydraulic Power Output Valves	4			
Lifting Capacity (kg)	2600			
Three Point Hitch System	Category II			
POWER TAKE OFF				
Type	Independent Double Speed			
Pto (rpm)	540 (1956)			
Pto (rpm)	540E (1506)			
BRAKES				
Type	Oil Bath Disc Brake			
Foot Brake	Mechanically Controlled			
Hand Brake	Mechanically Controlled			
TYRES				
1. Option (Front)	7,50 - 16	11,2 - 24	7,50 - 16	11,2 - 24
1. Option (Rear)	13,6 - 36	13,6 - 36	13,6 - 36	13,6 - 36
2. Option (Front)	7,50 - 16	11,2 - 24	7,50 - 16	11,2 - 24
2. Option (Rear)	16,9 - 30	16,9 - 30	16,9 - 30	16,9 - 30
3. Option (Front)	-	11,2 - 24	-	11,2 - 24
3. Option (Rear)	-	13,6 - 38	-	13,6 - 38
DIMENSIONS (mm)				
Length	3830	3930	3830	3930
Height	2685		2555	
Wheelbase	2105	2215	2105	2215
Track Width (Front) (mm)	1370 - 1570	1380	1370 - 1570	1380
Track Width (Rear) (mm)	1320 - 1520	1320 - 1520	1320 - 1520	1320 - 1520
Ground Clearance	460	460	460	460
WEIGHTS (kg)				
Front Weights	4x30 + 50	6x30 + 50	4x30 + 50	6x30 + 50
Rear Weights	2x(47+54)			
Total Weight (Without Ballasts)	2820	3080	3025	3285